


Smart Ear & Forehead Thermometer



Specifications

_	
Model number	JPD-FR409-BT
Power	Internal Power Supply (DC 3V)
Battery	AAA x 2 (Alkaline dry battery for around 20,000 measurements)
Display	Segment LCD
Measuring range	Forehead mode: 22.0°C-43.0°C (71.6°F-109.4°F)
	Ear mode: 34.0°C–43.0°C (93.2°F–109.4°F)
	Object mode: 0.0°C-100.0°C (32.0°F-212.0°F)
Accuracy (laboratory)	Forehead: ±0.2°C (36.0°C-39.0°C) ; ±0.3°C (22.0°C-36.0°C / 39.0°C~43.0°C);
	Ear mode: ±0.2°C (36.0°C-39.0°C) ; ±0.3°C (34.0°C-36.0°C / 39.0°C~43.0°C);
	Object mode: ±1.0°C/±2.0°F
Service life	2 years
Resolution	0.1°C (0.1°F)
Measuring site	Ear canal, Forehead (keep 1~3 cm from forehead)
Low-battery alert	The low-battery symbol is displayed if the power voltage is lower than 2.5 V \pm 0.1V
Dimensions & weight	155.2×39.6×49.1mm - Thermometer (with batteries): 101 g
Operating environment	Temperature: 10°C~ 40°C (50°F–104°F) Humidity: 15%–95% RH, non-condensing
	Atmospheric pressure: 86–106 kPa
Storage and	RH: 15% - 95% non-condensing- Temperature -20°C - +50°C -
transportation	Athmospheric pressure 50kPa - 106kPa

Structure



LCD display screen
Indicator
Power button / Measure button
Adult mode / Child mode
Mode button (Forehead / Ear / Object)

kinetik

Kinetik Medical Devices Ltd Unit 3 Perrywood Business Park, Honeycrock Lane, Surrey RH1 5DZ www.kinetikwellbeing.com

#BeWellStayWell