



Features

- Clinically Validated
- Share with your Doctor
- Easy to Use
- Accurate SpO₂ Measurement
- Bluetooth Sync
- Auto Power Off











LED display screen

Specifications

Model Number	JPD-500G	
Dimensions	58.0 mm × 32.0 mm × 32.9 mm	Battery Battery cover lock
Weight	50.4 g (including two AAA dry batteries)	
Bluetooth module	4.0	
Normal working condition	Working Temperature: 5°C to 40°C (41°F to 104°F)	
	Relative Humidity: 15% to 80%, non-condensing	
	Atmospheric Pressure: 70 kPa to 106 kPa	
	Rated Voltage: DC 3.0 V	
Display range	Oxygen Saturation: 35% to 100%	
	Pulse rate: 25 bpm to 250 bpm	
Resolution	Oxygen Saturation: 1% Pulse rate: 1bpm	
Measurement precision	Oxygen Saturation: ±2% (70% to 100%)	
	No requirement (≤69%)	
	Pulse rate: ±2 bpm	
Storage and transportation	Temperature: -10°C - 50°C (14°F-122°F)	
	Relative humidity: 10%-93% (no condensation)	
	Atmospheric pressure: 50kPa–106 kPa.	
Waterproof grade	IP22	

Structure

